PASSPORT READERS & ID SCANNERS

COMBO SCAN KIOSK an dem id scanner

Low profile and simple shape device, ideal for integration



Smooth passenger- and visitor flow through an integrated self-service airport kiosk or automated visitor management gate – this is what Combo Scan Kiosk provides. The scanner can also be used in many other applications such as any CUSS system, ATMs, check-in kiosks, railways and cruise terminals or even in tobacco- and alcohol vending machines where service is age-restricted.

The reader's low profile and simple shape makes it ideal for integration. Its intuitive design greatly helps infrequent visitors who are typical in the self-service environment.

It can save up to 3-4 minutes per visitor while you also benefit from the 100% accurate customer data including recognition of international IDs too. It adds an extra layer of security to every business in those application areas where checking identity documents is a must but there is no human staff attendance. Operates from a single USB connection and comes with mounting points for secure integration.





Main benefits

- · Profit from accurate data entry in self-service applications
- Intuitive design helps infrequent visitors
- · Be compliant to privacy and security regulations
- Automated and high accuracy system with 24/7 operation
- Enhance your corporate by smooth visitor flow

Adaptive Recognition America Adaptive Recognition Hungary Adaptive Recognition **Nordic** Adaptive Recognition **Singapore** SENDINFO@ARH.HU WWW.ADAPTIVERECOGNITION.COM

Combo Scan Kiosk

Specifications

 MRZ OCR reading of ID-1/ID-2/ID-3 documents • 1D and 2D barcode reading • 500 PPI glare-free imaging • compact & USB-powered • various OCR engines available to read foreign characters • no moving parts, maintenance-free operation

Imaging


| Active Scan Area | 125 mm × 55 mm (4.92" × 2.17") |
|----------------------|--|
| Illumination Sources | LED visible white, IR (B900) |
| Image Resolution | 500 PPI |
| Provided Images | Visible, IR, OVD image, glare-free image |
| Image Formats | BMP, JPG, JPG2000 and PNG |
| Image Color Depth | 24 bits/pixels [RGB, 8 bits/pixels (IR image)] |
| | |


Reading Capability

| Automatic Document Detection (ADD) | YES |
|------------------------------------|---|
| Reflection Removal (RR) | YES |
| Adaptive Light Control | YES |
| ICAO MRZ Reading | ICAO compliant documents per ICAO 9303 specification Part 1, Part 1, v2, Part 2, Part 3 and Part 3, for Type ID-1, ID-2 and ID-3 MRZ Optical Character Recognition |
| VIZ Reading | Available with VIZ OCR software for ID-1 size documents |
| Barcode Reading | 1D: UPC-A, EAN8, EAN13, Code39, Code128 and ITF 2D: PDF 417, Data Matrix, QR Code, Aztec Code From paper based documents and mobile devices AAMVA compliant PDF417 and IATA BCBP |

PROGRAMMING & INTERFACES


| Supported Operating Systems | Windows 7, 8, 8.1, 10 + Linux (ask for details) |
|----------------------------------|--|
| Software Development Kit (SDK) | Complete SDK including DLLs and demo programs |
| Programming Languages | C/C++, C#, Visual Basic 6.0, Delphi, VB.NET, Java |
| General Interfaces | AR's native, Twain and Accuant |
| PC Connection | USB 2.0 high speed (USB 3.0 compatible) |
| Advanced Document Authentication | Module - Data consistency checks: MRZ, VIZ, RFID, barcodes etc |
| Internal Memory | Storing factory calibration |
| Firmware Upgrade | Automatic, via USB |





Mechanical and Other Data

| Size (width \times depth \times height) | 150 mm × 123 mm × 67.5 mm (5.9" × 4.84" × 2.66") |
|---|--|
| Weight | 0.6 kg (1.32 lbs.) |
| Operating Temperature | 5 °C to 45 °C (45 °F to 113 °F) |
| Operating Humidity | 0-95 % (non-condensing) |
| Power supply | From USB, no external power supply is required |
| Case | Metal case |
| Window glass | 4 mm tempered glass |
| Compliances | FCC, CE, WEEE, RoHS |
| Maintenance | No moving parts, maintenance-free operation |
| Warranty | 3-year warranty, upgradeable |
| | |



Technical specifications are subject to change without prior notice. This document does not constitute an offer.

Adaptive Recognition America Adaptive Recognition Hungary

Adaptive Recognition Nordic Adaptive Recognition Singap Adaptive Recognition Singapore

SENDINF0@ARH.HU WWW.ADAPTIVERECOGNITION.COM